

GLC SERIES

GRADE
2

COMMERCIAL CYLINDRICAL DEADBOLT

The GLC560 and GLC562 auxiliary deadbolts add style and security to any door. They can be keyed to match any GLC or GAL lockset.



FEATURES


- Certification: UL R26058(mfg. 9082ET)Grade 2 ANSI A156.5
- Door Thickness: 1 3/4" - 2"
- Adjustable Backset: 2 3/4" - 2 3/8"
- Bolt: Heavy duty 1" throw Steel reinforced non adjustable
- Face Plate: 1 1/8" x 2 1/4" for 2 3/4" bolt
- Rating: UL Rated R26058(mfg. 9082ET) for "A" label 3 hour door
- Strike: 1 1/8" x 2 3/4" with reinforcing and security screws
- Cylinder: Solid Brass 6 pin keyed to 5
- Keyway: Schlage "C" or IC less interchangeable core
- Function: Single and double cylinder
- Keying: KA4 - Standard
- Trim Ring: Solid security collar reinforced
- Warranty: Lifetime mechanical - 10 year finish
- Finish: US26D

OPTIONS

- GLC560UL-IC: interchangeable core single cylinder
- GLC562UL-IC: interchangeable core double cylinder

KEYING OPTIONS

- 2 keys per cylinder
- KD: Keyed Different
- KA: Keyed Alike
- KA2: Keyed alike; groups of 2
- KEYWAYS: SC6



DOOR PREP